

Product Specification

Ammonium Hydroxide, 5% (v/v)

| Lot Number: SAMPLE Prod | duct Number: 628 | | Manufacture Date: N/A Expiration Date: N/A |
|---|--|--|--|
| Name | CAS# | Grade | |
| Water | 7732-18-5 | ACS/ASTM/USP/EP | |
| Ammonium Hydroxide | 1336-21-6 | ACS | |
| Test | Specification | Result | NIST SRM# |
| Appearance | Colorless liquid | N/A | |
| Assay (vs. Sulfuric Acid/Methyl Red) | 4.9 - 5.1 % (v/v) | N/A | 723 |
| Specification | Reference | | |
| Ammonium hydroxide, 5% | TAPPI (T 618 cm-84) | | |
| Ammonium Hydroxide, 1+19 | APHA (3500-Mg D) | | |
| Ammonium Hydroxide (1+19) | ASTM (D 2187 H) | | |
| Volumetric glassware complies with Class A tole recalibrated regularly in accordance with ASTM traceable to the NIST national mass standard. T thermometer traceable to NIST standards. All pr methods. Batch records document raw material t Part Number | E 542 and NIST Procedure NBSIR 74-46 hermometers and temperature probes ar oducts are prepared according to master | 31. Balances are calibrated regu- re calibrated before first use and documents that assure manufa istory for each lot manufacture | larly with weights certified l recalibrated regularly with a acture according to validated |
| | | 24 months | |
| 628-1 628-16 | 4 L natural poly | 24 months 24 months | |
| 628-32 | 500 mL natural poly 1 L natural poly | 24 months 24 months | |
| 628-5 | 20 L Cubitainer® | 24 months 24 months | |
| 628-55 | | 24 months | |
| 040 00 | 55 gal poly drum | 24 III0110115 | |

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.