# RICCA CHEMICAL COMPANY®

Manufacture Date: N/A

186-I-g, 186-II-g, 191d

Expiration Date: N/A

## **Product Specification**

#### Buffer, Reference Standard, pH $7.00 \pm 0.01$ at 25°C (Color Coded Green)

Lot Number: SA	AMPLE
----------------	-------

**Product Number**: 1551.4

The certified value for this product is confirmed in independent testing by a second qualified chemist.

°C 0 5 10 15202530 35 40 45 50pН 7.127.09 7.067.047.027.006.996.98 6.98 6.97 6.97

Name	CAS#	Grade	
Water	7732-18-5	ACS/ASTM/USP/EP	
Sodium Phosphate Dibasic	7558-79-4	ACS	
Potassium Dihydrogen Phosphate	7778-77-0	ACS	
Preservative	Proprietary		
Yellow Dye	Proprietary		
Blue Dye	Proprietary		
Sodium Hydroxide	1310-73-2	Reagent	

Test	Specification	$\mathbf{Result}$	
Appearance	Green liquid	Green liquid	*Not a certified value.
Test	Certified Value	Uncertainty	NIST SRM#

6.990-7.010

0.02

#### pH at 25°C (Method: SQCP027, SQCP033)

pH measurements were performed in our Arlington, TX, Pocomoke City, MD, or Batesville, IN laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly to the NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Size / Package Type	Shelf Life (Unopened Container)
4 L natural poly	24 months
500 mL natural poly	24 months
4 L Cubitainer®	24 months
10 L Cubitainer®	24 months
1 L natural poly	24 months
20 L Cubitainer®	24 months
55 gal poly drum	24 months
	4 L natural poly 500 mL natural poly 4 L Cubitainer® 10 L Cubitainer® 1 L natural poly 20 L Cubitainer®

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

### This product was tested in an ISO 17025 Accredited Laboratory

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.