RICCA CHEMICAL COMPANY®										1Y [®]	1490 Lammers Pik Batesville, IN 4700 http://www.riccachemical.cor 1-888-GO-RICCA	
customerservice@riccachemical.com Certificate of Analysis Buffer, Reference Standard, pH 5.00 ± 0.01 at 25°C											astomerservice@riccachemical.com	
											Lot Number: 4312K20 Product	
		e for this p ble pH val	-		-		0.0	-			temperatures are accurate to ± 0.05 .	
°C pH	$\begin{array}{c} 10\\ 4.96\end{array}$	$\begin{array}{c} 15\\ 4.97\end{array}$	$\begin{array}{c} 20 \\ 4.98 \end{array}$	$\begin{array}{c} 25 \\ 5.00 \end{array}$	$\begin{array}{c} 30 \\ 5.01 \end{array}$	$\begin{array}{c} 35\\ 5.03\end{array}$	$\begin{array}{c} 40 \\ 5.04 \end{array}$	$\begin{array}{c} 45\\ 5.06\end{array}$	$\begin{array}{c} 50 \\ 5.08 \end{array}$			
Name				CAS#				Grade				
Water					7732-18-5			ACS/ASTM/USP/EP				
Potassium Acid Phthalate					877-24-7				Buffer			
Sodium Hydroxide					1310-73-2			Reagent				
Preservative					Proprietary							
Test							Spe	cificatio	n	Res	ult	

Appearance	Colorless liquid	Passed	*Not a certified value.	
Test	Certified Value	Uncertainty	NIST SRM#	
pH at 25°C (Method: SQCP027, SQCP033)	5.002	0.02	185i, 186-I-g, 186-II-g	

pH measurements were performed in our Batesville, IN laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387.02) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated before first use and recalibrated to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
1505-1	4 L natural poly	24 months
1505-16	500 mL natural poly	24 months
1505-2.5	10 L Cubitainer®	24 months
1505-32	1 L natural poly	24 months
1505-5	20 L Cubitainer®	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Faul Brandon

Paul Brandon (01/02/2024) Production Manager This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This product was tested in an ISO 17025 Accredited Laboratory

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.