RICCA CHEMICAL COMPANY®

Certificate of Analysis

Nitric Acid, 50% (v/v)

Lot Number: 1310U24 Product Number: 5350		Manufacture Date: NOV 01, 202 Expiration Date: OCT 202		
CAS#	Grade			
7732-18-5	ACS/AS	TM/USP/EP		
7697-37-2	ACS			
Specification		Result	NIST SRM#	
Colorless to light y	yellow liquid	Passed		
thalein) 49.7-50.3 % (v/v)		50.3 % (v/v)	84	
	Reference			
	ASTM (D 2907 A)			
	ASTM (D 2972 A)			
	ASTM (D 3859 B)			
	ASTM (D 2972 B)			
	ASTM (D 1091)			
	APHA (3030 F)			
	APHA (3113 B)			
	ASTM (D 4453)			
	ASTM (D 3559 D)			
	EPA (SW-846) (6010B)			
	ASTM (D 808)			
	EPA (200.7)			
	EPA (METALS)			
	ASTM (D 4190)			
	ASTM (D 3865)			
	ASTM (D 5811)			
	ASTM (D 4309)			
	ASTM (D 1498)			
	ASTM (D 3697)			
	CAS# 7732-18-5 7697-37-2 Specification Colorless to light y	CAS#Grade7732-18-5ACS/AS7697-37-2ACSSpecificationColorless to light yellow liquidthalein)49.7-50.3 % (v/v)ReferenceASTM (D 2907)ASTM (D 2972)ASTM (D 2972)ASTM (D 2972)ASTM (D 2972)ASTM (D 2972)ASTM (D 1091)ASTM (D 1092)ASTM (D 302)ASTM (D 303)ASTM (D 303)ASTM (D 303)ASTM (D 304)ASTM (D 304)ASTM (D 4304)ASTM (D 4304)ASTM (D 4304)ASTM (D 4304)ASTM (D 4304)ASTM (D 4304)ASTM (D 1494)ASTM (D 1494)	CAS# Grade 7732-18-5 ACS/ASTM/USP/EP 7697-37-2 ACS Specification Result Colorless to light yellow liquid Passed thalein) 49.7-50.3 % (v/v) 50.3 % (v/v) Reference ASTM (D 2907 A) ASTM (D 2972 A) ASTM (D 2972 A) ASTM (D 2972 B) ASTM (D 1091) APHA (3030 F) APHA (3113 B) ASTM (D 4453) ASTM (D 4453) ASTM (D 3559 D) EPA (SW-846) (6010B) ASTM (D 808) EPA (200.7) EPA (METALS) ASTM (D 4190) ASTM (D 4309) ASTM (D 4309) ASTM (D 4309) ASTM (D 4309)	

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)		
5350-16	500 mL safety-coated glass	24 months		
5350-32	1 L safety-coated glass	24 months		
5350-5PT	2.5 L safety-coated glass	24 months		
P _{common} dod S _{tomo} r_{c} : 15% - 20% (z_{0})				

Recommended Storage: 15°C - 30°C (59°F - 86°F)

421.

Heidi J Green (11/01/2023) Operations Manager This document is designed to comply with ISO Guide 31 "Reference Materials --Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.