

# Certificate of Analysis

## Fluoride Standard, 10 ppm F<sup>-</sup> (Premixed with TISAB / Color Coded Orange)

**Lot Number:** 4404R14

**Product Number:** 3165

**Manufacture Date:** MAY 01, 2024

**Expiration Date:** APR 2025

The certified value reported is the prepared value based upon the method of preparation of the material. The uncertainty in the prepared value is based upon the volumetric method of preparation.

The concentration is confirmed by Fluoride ISE and is certified traceable to NIST SRM 2203.

Directions for Use: This standard is premixed with TISAB. Do not dilute or add TISAB to this standard. After calibrating with this standard, mix test samples for analysis with an equal volume of Total Ionic Strength Adjustment Buffer, RICCA Cat. No. 8670. Read Fluoride concentration directly (no dilution factor).

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Sodium Chloride	7647-14-5	ACS
Sodium Hydroxide	1310-73-2	Reagent
Sodium Fluoride	7681-49-4	High Purity
1,2-Cyclohexylenediamine Tetraacetic Acid (CDTA)	13291-61-7	ACS
Acetic Acid	64-19-7	ACS
Preservative	Proprietary	
Yellow Dye	Proprietary	

Test	Specification	Result
Appearance	Orange liquid	Passed
Fluoride (F)	9.95-10.05 ppm	10.00 ppm

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
3165-1	4 L natural poly	12 months
3165-32	1 L natural poly	12 months

**Recommended Storage:** 15°C - 30°C (59°F - 86°F)



Paul Brandon (05/01/2024)

Production Manager

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.